

## **History of Construction**

### **Intermountain Power Wastewater Basin (UT00468) CCR Surface Impoundment**

**October 17, 2016**

**History of Construction for Intermountain Power Wastewater Basin (UT00468)  
40 CFR Part 257.73(c) and R315-319.73(c)**

**Owner/Operator Name and Address**

Intermountain Power Service Corporation (Operator)  
850 West Brush Wellman Rd.  
Delta, UT 84624

**Name and Identification Number**

Intermountain Power Wastewater Basin (UT00468), hereafter referred to in this report as "Wastewater Basin".

**Location of CCR Unit**

The Wastewater Basin is located in parts of the SW1/4 of SE1/4 of Section 14 and parts of the NWw1/4 of NE1/4 of Section 23, all Township 15 South, Range 7 West, Salt Lake Base and Meridian. [USGS Rain Lake 7½ minute topographic quad map (see Exhibit #1)]

**Statement of the purpose for which the CCR Unit is being used**

The Wastewater Basin has the following purpose: receive flue gas emission control residuals and other process material including process water separated for re-use, wash down, coal pile fun-off, boiler blowdown, cooling tower blowdown, regenerant rinsate, blowdown, etc. Water that accumulates in the Wastewater Basin is decanted and pumped back to the units where it can be used as make-up water for the sulfur dioxide removal system, pumped to the Ash Water Recycle Basin where it can be used as make-up water for the ash water system, or pumped to the Evaporation Ponds.

**Name and Size in acres of the watershed within which the CCR Unit is located**

This CCR unit (Wastewater Basin (UT00468) is situated in the Sevier River Watershed, more specifically USGS hydrologic unit (HUC) 16030005, Lower Sevier. Per the National Resource Conservation Service (NRCS), the Lower Sevier hydrologic unit comprises approximately 4,094 square miles, or about 2,620,563 acres. This CCR unit is not located on a waterway, it is located off- channel and has a perimeter dike. The contributing drainage area to Intermountain Wastewater Basin is limited to this basin's total impoundment area (approximately 53 acres) because the perimeter dike prevents surface water run-on from adjacent land.

### Physical and Engineering properties of the foundation and abutment materials on which the CCR Unit is constructed

Construction records for this CCR unit are sparse. Construction of the Intermountain Power Project (IPP) started in about 1981. Available drawings for IPP's impoundment/ponds and embankments are dated 1983. The IPP was commissioned in 1986. There are no records which could be found of the original geotechnical design or material properties for the foundation and abutments on which the Bottom Ash Basin was constructed. However, several site-specific geotechnical investigations and studies for the plant site and CCR surface impoundments were available for review. From these studies, it appears that the CCR surface impoundment embankments were constructed of on-site natural soils. The on-site soils consist primarily of silty sand and sandy silts, but may also contain clean sands and lean clay.

### Type, size, range, and physical, and engineering properties of materials used in constructing each zone or stage of CCR Unit

A review of the very limited material available indicates that the upper CCR surface impoundment embankments appear to be constructed of compacted fill (local borrow) material derived from on-site native soils, which, based on test holes drilled in the embankment generally consist of Clayey Sand (SC, SP-SC) and poorly graded sand (SP). The lower portion of the embankment consists of compacted native, in-place (non-fill) soils, which based on test holes drilled in the embankment, generally classify as poorly graded sand (SP) and silty sand (SM). At a depth below the floor of the basin there are various strata including a fairly continuous layer of sandy lean clay (CL). Other than the fill and natural portions of the embankment, there appears to be no explicit zonation of materials or special foundation treatments. The embankments were constructed in horizontal layers not exceeding 8 inches in uncompacted thickness. Each layer had a compacted density of at 90% of the maximum density within a range of  $\pm 2\%$  of the optimum moisture content as determined by ASTM 1557.

### Detailed Dimension Drawings of CCR Unit

- Drawings of CCR unit - See Exhibit #2.
- Foundation improvements- There have not been any changes in the foundation since initial construction.
- Drainage provisions- There are no drainage provisions present since off-channel surface impoundment.
- Spillways - There are no spillways since off-channel impoundment.
- Diversion ditches - There are no diversion ditches since off-channel impoundment.
- Outlets - See Exhibit #3.
- Instrumentation locations - See Exhibit #4.
- Slope Protection- Slopes have been seeded with a grass seed mixture

- Operating Pool surface elevation following peak discharge from the inflow design flood - about 2 inches above the maximum water surface since this is an off channel impoundment and the only water that would come in would be from a 100 year storm event which would be about 2 inches. Since there is 3 feet nominal of free board, this should not be an issue.
- Expected maximum depth of CCR within the CCR surface impoundment- CCR material can be as high as the maximum water surface in this CCR unit.
- Identifiable natural or manmade features that could adversely affect operation of the CCR Unit - There are no identifiable features that could affect operation.

#### Description of the type, purpose, and location of existing instrumentation

Instrumentation for the Wastewater Basin consists of staff gauges and monitoring wells. The monitoring wells are located around the perimeter of the Wastewater Basin at the toe of the embankment. The wells are measured manually with a level indicator frequently to indicate any leakage from the Wastewater Basin. Staff Gauges are manually read to monitor levels.

#### Area Capacity Curves

Area Capacity Table - See Exhibit #5.

#### Description of each spillway and diversion design features

The Waste Water Basin does not have a spillway because of controlled inflow/outflow operation. It is not located on a waterway, it is located off-channel.

#### Construction specifications and provisions for surveillance, maintenance, and repair of the CCR Unit

Manual inspections of the Wastewater Basin are conducted regularly. As required under the CCR rule, the Wastewater Basin is inspected by a qualified person at intervals not exceeding 7 days. The Wastewater Basin's instrumentation is monitored by a qualified person at intervals not exceeding 30 days. In addition, the Wastewater Basin is inspected by a professional engineer on an annual basis. Any maintenance or repair items are reported and submitted by personnel conducting inspections. Any needed repairs are done as quickly as reasonably possible. It is also inspected by the Utah State Engineer's office every five years.


#### Any record or knowledge of structural instability of the CCR Unit

No known record or knowledge of structural instability for the Wastewater Basin. All of the inspections have indicated that the Wastewater Basin is structurally stable.

**Exhibit #1**

**Location of CCR Unit**






11 12 13 14 15 16  
 17 18 19 20 21 22  
 23 24 25 26 27 28  
 29 30 31 32 33 34  
 35 36 37 38 39 40  
 41 42 43 44 45 46  
 47 48 49 50 51 52  
 53 54 55 56 57 58  
 59 60 61 62 63 64  
 65 66 67 68 69 70  
 71 72 73 74 75 76  
 77 78 79 80 81 82  
 83 84 85 86 87 88  
 89 90 91 92 93 94  
 95 96 97 98 99 100


**Exhibit #2**

**Drawings of CCR Unit**






SECTION 2  
SCALE: 1/4" = 1'-0"




ELEVATION LOOKING NORTH AND SOUTH  
SCALE: 1/4" = 1'-0"


ELEVATION LOOKING EAST AND WEST  
SCALE: 1/4" = 1'-0"




SECTION 1  
SCALE: 1/4" = 1'-0"



BASEPLATE PLAN  
SCALE: 1/4" = 1'-0"



PLAN  
SCALE: 1/4" = 1'-0"





PLAN AT 0.4500  
SCALE: 1/4" = 1'-0"




DESIGNED BY: [Name]  
 CHECKED BY: [Name]  
 DATE: [Date]

PROJECT NO.	6255 - BRSU-33842
DATE	
SCALE	AS NOTED
DESIGNER	PPS
CHECKER	PPS
APPROVER	PPS
CONTRACT	CONCRETE-REINFORCED PLATE BEAM PUMP BLOC
PLANS	PLANS, SECTIONS, AND DETAILS






TYPICAL BRIDGE DECK AND ANCHORAGE DETAIL



TYPICAL SYNTHETIC LINER PIPE PENETRATION DETAIL, TYPE 1, 2 & 3











**GENERAL NOTES**

1. CONTRACTOR SHALL VERIFY ALL DIMENSIONS AND CONDITIONS BEFORE COMMENCING WORK.
2. ALL MATERIALS SHALL BE OF THE BEST QUALITY AVAILABLE AND SHALL BE SUBJECT TO INSPECTION AND APPROVAL BY THE ENGINEER.
3. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS OF THE STATE OF TEXAS.
4. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS.
5. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS OF THE STATE OF TEXAS.
6. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS.
7. ALL WORK SHALL BE DONE IN ACCORDANCE WITH THE STANDARD SPECIFICATIONS FOR PUBLIC WORKS OF THE STATE OF TEXAS.



PROJECT NO. 8255 - 83TU - 53080	
DATE: 11/15/50	SCALE: AS NOTED
DESIGNED BY: [Name]	
CHECKED BY: [Name]	
APPROVED BY: [Name]	
TITLE: BRIDGE AND ANCHORAGES	
SECTION AND DETAILS	



NOTED:  
 1. SEE EACH DRAWING FOR SPECIAL NOTES.  
 2. THE CONTRACTOR SHALL VERIFY THAT THE LINER IS PROPERLY INSTALLED AND THAT THE JOINTS ARE PROPERLY SEALED.  
 3. THE CONTRACTOR SHALL VERIFY THAT THE LINER IS PROPERLY ANCHORED TO THE CONCRETE STRUCTURE.  
 4. THE CONTRACTOR SHALL VERIFY THAT THE LINER IS PROPERLY SLOPED AND THAT THE JOINTS ARE PROPERLY SEALED.



SCHEMATIC NOTED

PROJECT NO.	0206-9870-5308
PROJECT NAME	PROJECT NAME
DATE	DATE
SCALE	SCALE
DESIGNED BY	DESIGNED BY
CHECKED BY	CHECKED BY
APPROVED BY	APPROVED BY
DATE	DATE
PROJECT NO.	0206-9870-5308
PROJECT NAME	PROJECT NAME
DATE	DATE
SCALE	SCALE
DESIGNED BY	DESIGNED BY
CHECKED BY	CHECKED BY
APPROVED BY	APPROVED BY
DATE	DATE


**Exhibit #3**

**Drawing of Outlets**



**Exhibit #4**

**Instrumentation Locations**



CCR MONITORING  
INSTRUMENTATION



**Exhibit #5**

**Area Capacity Table**

# Grimshaw Surveying, Inc.

LAND SURVEYING & MAPPING

546 East Midvalley Road

Enoch, Utah 84721

phone (435) 586-9130

cell (435) 559-9130

January 14, 2016

Intermountain Power Service Corporation

850 W. Brush Wellman Rd.

Delta, Utah 84624-9546

## Waste Water Basin Capacity Table

Contour Elevation	Water Depth	Volume in Acre Feet
4650	22	917
4649	21	866
4648	20	815
4647	19	765
4646	18	716
4645	17	667
4644	16	618
4643	15	570
4642	14	522
4641	13	474
4640	12	427
4639	11	380
4638	10	334
4637	9	287
4636	8	242
4635	7	197
4634	6	152
4633	5	108
4632	4	64
4631	3	28
4630	2	8.5
4629	1	1.3
4628	0	0

Douglas B. Grimshaw, PLS

